

Information Bulletin

Tablet Requirements

for H2O, 300, 600, & 700 Series Automatic Applicators

As an industry leader in baler moisture sensors and precision preservative applicators, Harvest Tec continues to develop systems utilizing tablet technology. As of 2017, Harvest Tec utilizes Apple iPads and Android tablets for control of various systems using the charging cable for power and data transfer. This bulletin highlights key requirements for tablet usage.



- ANDROID TABLETS SHOULD BE A REPUTABLE BRAND LIKE SAMSUNG (**NOT A CHEAP ONE FROM AMAZON – CHECK WITH HT IF UNSURE**)
- Tablets should utilize quality cables capable of charging and data transfer.
- HT Provided or original charging/data transfer cables are preferred. Replacements should be of equal quality to allow for proper data transfer.
- Low-cost replacement cables **NOT** supported.
- USB-A to USB-C cables can be utilized. USB-C cables with adapters are **NOT** supported.
- iPad 1st Gen with wide plug **NOT** supported.



030-6672C - IIC for 300 & 600 Series (**HAY APP**)



006-6673 - ICM for 700 series (**PRECISION BALING APP**)

006-2473 - Module for H2O kits (**H2O APP**)



Charging cables with adapters not supported



1ST Generation iPads are not supported



PREFERRED

iPad with original lightning charging cable is preferred



PREFERRED

Harvest Tec provided cables are preferred

iPad 6th generation (or newer) using USB-C to USB-A can be



OK

Contact Harvest Tec if there is an Apple iPad compatibility question for use with your Harvest Tec Device

Field ready iPad Mini Options from Harvest Tec

- 030-6670DK – iPad mini 6 (refurbed) with case, spring loaded cradle RAM Mount with suction mount, preferred data transfer charging cable, and all Harvest Tec apps preloaded

Field Ready Android Options from Harvest Tec

- 030-1670DK – Samsung Galaxy Tab A9 with case, spring loaded cradle RAM Mount with suction mount, preferred data transfer charging cable, and all Harvest Tec apps preloaded

Approved charging cable options from Harvest Tec

- 006-6672USBC – 6' Apple Lightning plug to USB-A (for use with older iPad & iPad Mini, Gen 2 thru Gen 5).
- 006-6672USBX – 6' USB-C plug to USB-A plug (for use with iPad 6th generation and newer).

Supported Tablet Operating Software – Hay App **(300/600 Series)**

- Apple iOS versions 12 through 26

Supported Tablet Operating Software – Precision Baling App **(700 Series)**

- Apple iOS versions 12 through 26
- Android versions 5 through 15 **(NO CHEAP OFF BRAND TABLETS)**

Phone Compatibility **(H2O ONLY)**

- Apple iOS versions 12 through 26
- Android versions 5 through 15
 - Google Pixel phones **NOT** compatible

5/14/26

For more information, contact Harvest Tec

www.harvesttec.com

715.386.9100