



Information Bulletin

iPad Requirements

for H2O, 300, 600, & 700 Series Automatic Applicators

As an industry leader in on baler moisture sensors and precision preservative applicator Harvest Tec continues to develop systems utilizing tablet technology. As of 2017 Harvest Tec utilizes Apple iPads for control of various systems using the charging cable for these tablets. This bulletin highlights key requirements for Apple tablet usage.



- Tablets using Apple lightning cables should be utilized
- iPad original charging cable preferred
- Low cost replacement cables NOT supported
- iPad 6th generation with USB-C to USB-A cable can be utilized. USB-C cables with adapters are NOT supported
- iPad 1st Gen with wide plug NOT supported
- iPad Pro devices are NOT supported



030-6672C - IIC for 300 & 600 Series (**HAY APP**)



006-6673 - ICM for 700 series (**PRECISION BALING APP**)

006-2473 - Module for H2O kits (**H2O APP**)



PREFERRED

iPad with original lightning charging cable is preferred



OK

iPad 6th generation using USB-C to USB-A can be used



Charging cables with adapters not supported



1ST Generation iPads not supported

Contact Harvest Tec if there is an Apple iPad compatibility question for use with your Harvest Tec Device

Field ready iPad mini options from Harvest Tec

- 030-2670DK – iPad mini 2 (refurbed) with case, spring loaded cradle RAM Mount, and app preloaded
- 030-4670DK – iPad mini 4 (refurbed) with case, spring loaded cradle RAM Mount, and app preloaded

Approved charging cable options from Harvest Tec

- 006-6672USBC – 6' Apple Lightning plug to USB-A (for use with most iPad & iPad mini Gen 2 and later).
- 006-6672USBX – 6' USB-C plug to USB-A plug (for use with iPad 6th generation).

Contact Harvest Tec for more info www.harvesttec.com 715.386.9100

*The Hay app, H2O app, and Precision Baling App Require the Current iOS Operating System for Apple or one Version Previous